

# TEST REPORT

Prepared For

**#ULA1L PTY LTD**

#2/63 Industrial Dr, Braeside VIC 3195

**#Model: ECO-BT24W-1200-D**



<b>Report Type:</b>	Report is prepared for the client above to present the result of measured temperature of samples and projected lumen maintenance life of LED lighting product according to projecting method from IES: IES TM-21-19
<b>Reviewed By:</b>	Hexy He <i>Hexy He</i>
<b>Report Number:</b>	DG5220916-42257E-EE
<b>Test Date:</b>	2022-09-28
<b>Report Date:</b>	2022-10-10
<b>Approved by:</b>	Blake Zhang / EE Engineer
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 5/F(B-West) -7/F, the 3rd Phase of Wan Li Industrial Building D, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China. Tel: +86-755-33320018 Fax: +86-755-33320008
<b>Test Facility:</b>	Test facility was located at No.12, Pulong East 1 <sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China.

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.(Shenzhen). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

## 1. General Description<sup>#</sup>

### Information of Final Products:

One test sample was in good condition and received on 2022-09-16 and used for testing. All tests and evaluations were performed at the lowest CCT.

Model Number:	ECO-BT24W-1200-D
Model Name:	LED Batten Light
Brand Name:	
Manufacturer:	ULA1L PTY LTD
Rated Voltage:	220-240V 50/60Hz
Test Voltage:	230V, 50 Hz
Rated Power:	24W
Series-Parallel:	(3P48S)*2
Number of LED chips:	288
Average drive current:	52.7mA
Total drive current:	158mA
Driver Brand:	
Driver Model:	MC24W MS CCT

### Remark:

There are 288pcs LED chip(s) (3P 48S)\*2 in models ECO-BT24W-1200-D.

The total measured current of driver output is 158mA, and current on each parallel was 52.7mA (158mA/3=52.7mA), since the forward current on each LED chip(s) in the same series was equivalent, so forward current on each LED chip(s) was 52.7mA.

### <sup>#</sup>Information of LED Light Source:

Model Number of LED Light Source:	2835 0.5W 150mA
Type of LED Components:	LED Package
Manufacturer:	HuNan Pusiasat Opto Technology Co.,LTD
LM-80 Report No:	RSZ161129514-10-9000

## 2. Standards Used

- IES TM-21-19 Projecting Long Term Lumen Maintenance of LED Light Sources(This method is not in NVLAP accreditation scope)
- ANSI/UL 1598-2008: Standard for Safety of Luminaires
- Annex A of IES LM-84-14 Recommendations for measurement of IN-SITU conditions LED case temperature

## 3. Test Method

Lumen maintenance life of LED light source and LED lamp or luminaire (if any) is the elapsed operating time over which an LED light source maintains a given percentage of its initial light output.  $L_{70}$  in this report is the time (in hours) when the light output from the LED has dropped to 70% of its initial output.

The LED light source is LED package, array, or module which is tested in IES LM-80-15 test report. Final product means LED lamp or luminaire which the LED light source will be included.  $TMP_{LED}$  is the temperature of the

thermocouple attachment point on the LED light source package as defined by the manufacturer of the LED light source. The *in situ* temperature of LED light source used in final product was used to calculate the lumen maintenance life of final product, if any.

The *in situ* temperature is measured according to ANSI/UL 1598 and IES LM-84 Annex A. The LED which has the highest temperature was measured at the location of LED case which is specified by LED source manufacturer and detailed by LM-80 report. The hottest LED was found by the following procedure:

An IR thermography may be used to find the hottest LEDs. Or if the layout of PCB is symmetrical, the hottest LED should be at the center or close to the center of the array. Or in question, more than one TMP should be measured to find out the hottest LED. The case temperature of the hottest LED source at *in situ* condition is reported and is used to project  $L_{70}$  life time.

The reported temperature value for each point should be the readings of the hybrid recorder after the temperature of each point is stabilized and constant. A temperature is considered constant if the test has been running for at least 3 hours; and three successive readings, taken at 15-minute intervals, are within 1 degree C of one another and are not rising. Or the test was run for a minimum of 7.5 h. Ambient temperature variations above or below 25 °C have been respectively subtracted from or added to temperatures recorded at points on the device.

The drive current of LED package/module/ array was calculated as the total output current of the driver measured by multimeter, divided by the number of branches in parallel of LEDs.

The calculation of the  $L_{70}$  life is according to IES TM-21-19.

#### 4. Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
Multimeter	FLUKE	17B	1573 1328	2022-06-07	2023-06-06
Hybrid Recorder	YOKOGAWA	DR240	10#	2022-01-05	2023-01-04
AC POWER SUPPLY	HengPu	HPA 1103	0003394	2022-01-05	2023-01-04
Thermography	FLIR	E60	49037877	N/A	N/A


Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

## 5. In situ Temperature and Driver Current Measurements of Final Product

IR thermograph from hot PCBAs of Sample



Temperature measurement point on TMP<sub>LED</sub>



Temperature Measurement Data

### Test Condition

Ambient Temperature: 25°C±5°C

Relative Humidity: 58%

Supply voltage: 230V 50Hz

Type of thermocouples: T

Test Duration: ≥3.5Hours

### Test Result

Hottest TMP<sub>LED</sub>: 45.9° C

Forward Current(I<sub>F</sub>): 52.7mA


## 6. Lumen Maintenance Data of LED Light Source from LM-80 Report

Test Data for 85°C Case Temperature		Test Data for 105°C Case Temperature	
Time (hours)	Lumen Maintenance (%)	Time (hours)	Lumen Maintenance (%)
1000	100.16	1000	99.89
2000	99.92	2000	99.61
3000	99.67	3000	99.32
4000	99.45	4000	99.05
5000	99.22	5000	98.76
6000	98.98	6000	98.49
7000	98.70	7000	98.15
8000	98.50	8000	97.88
9000	98.28	9000	97.58

## 7. Calculate Result of Life Time Projection

Temperature Interpolation at 45.9° C (projection based on in-situ temperature entered)	
$T_{s,1}$ (°C)	85.00
$T_{s,1}$ (K)	358.15
$\alpha_1$	2.396E-06
$B_1$	1.004
$T_{s,2}$ (°C)	-
$T_{s,2}$ (K)	-
$\alpha_2$	-
$B_2$	-
$E_a/k_b$	-
A	-
$B_0$	1.004
$T_{s,i}$ (°C)	45.90
$T_{s,i}$ (K)	319.05
$\alpha_i$	2.396E-06
<b>Reported <math>L_{70}(9k)</math> at 45.9°C (hours)</b>	<b>&gt;54000</b>

## 8. Final Product Photo











## Directions

1. The information marked “superscript #” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
2. This report includes some test methods are not in NVLAP accreditation scope marked \*.
3. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $K=2$  with the 95% confidence interval.
6. This report cannot be reproduced except in full, without prior written approval of the Company.
7. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

\*\*\*\*\*END OF REPORT\*\*\*\*\*