

Measurement of Lamp Circuit Power for Luminaire

Prepared For

#ULA1L PTY LTD
#2/63 Industrial Dr, Braeside VIC 3195

#Model: ECO-BT24W-1200-D



Report Type:	IPART Lighting Requirements Guide – Commercial Lighting V2.2 Lighting Requirements Guide – Home Energy Efficiency Retrofits V1.4 VEET - Version 1.9 –16 December 2021 (Reference: C/18//24088)
Reviewed By:	Hexy He <i>Hexy He</i>
Report Number:	DG5220916-42074E-EE-1
Test Date:	2022-09-22
Report Date:	2022-10-10
Approved by:	Bill Xiong / EE Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 5/F(B-West) -7/F, the 3rd Phase of Wan Li Industrial Building D, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China. Tel: +86-755-33320018 Fax: +86-755-33320008
Test Facility:	Test facility was located at No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China.

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.(Shenzhen). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

1. General Information[#]

Information of Final Products:

One test sample was in good condition and received on 2022-09-16, and used for testing. All tests and evaluations were performed at the lowest CCT.

Model Number: ECO-BT24W-1200-D
Model Name: LED Batten Light
Brand Name: 
Manufacturer: ULA1L PTY LTD
Rated Voltage: 220-240V 50/60Hz
Rated Power: 24W
Driver Brand: 
Driver Model: MC24W MS CCT

2. Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
Digital power meter	YOKOGAWA	WT310	13398	2022-01-05	2023-01-04
Precision frequency power supply	ALL Power	APW-105N	970613	2022-01-05	2023-01-04


3. Test Standard

- IES LM-79-08 Electrical and Photometric Measurements of Solid-State Lighting Products
- IEC 62301:2011 Household electrical appliances – Measurement of standby power

4. Test Method

- Set up the test circuit according to the test circuit diagram below;
- Adjust the AC source to 230V/50Hz and operated for at least 30 minutes and repeat step three;

5. Test Circuit Diagram



6. Test Ambient


25.0°C, 50%RH

For model ECO-BT24W-1200-D, the lamp output were allowed to be stable conditions before measurements were taken.

7. Test Data

Model Number:		ECO-BT24W-1200-D					
Sample No.		DG5220916-42074E-S01					
Input					Output		
Voltage (V)	Frequency (Hz)	Current (A)	Wattage (W)	Power factor	Voltage (V)	Current (A)	Wattage (W)
230.1	50	0.1072	23.95	0.971	N/A	N/A	N/A

8. Final Product Photo







Directions

1. The information marked "superscript #" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
2. This report includes some test methods are not in NVLAP accreditation scope marked *.
3. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $K=2$ with the 95% confidence interval.
6. This report cannot be reproduced except in full, without prior written approval of the Company.
7. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

*****END OF REPORT*****